

SENIORSOFT SNS-OT07

Features

- USB or VGA interface available
- Easy for installation - one USB cable needed
- Best choice for space limited retail/hospitality settings

Specifications

Model	OT07SD	OT07SC
Display Area	53.6 x 86.64 mm.	
Standard Cabinet Color	Black	
Optimal Resolution	800 x 480 (WVGA)	
Brightness	200 cd/m (typ)	
Contrast Ratio	500:1(typ)	
Response Time	25ms (typ)	
LCD Viewing Angle (L/R/U/D)	70/70/50/60	
Tilt Angle	35°(V)/70°(-1)(w/polebase)	
Input Video signal connector	Mini Din 8 pins	USB
Power consumption	6W	2.5W
Input Frequency		
Power supply	DC 12V +/-10% /	DC 5V+/-10%
Temperature+		
Humidity		
Weight	500g(net)	
Physical Dimension	192 x 115 x 34.5 mm.	
Approvals	CE,FCC,BSMI	
Touch	N/A	
Wall Mounting		
Stand Base	Pole + Base	

This specification is subject to change without prior notice.



1. Sharp and Optimal LCD display size 153.6 x 86.64 mm.
2. Low power consumption only 6w or 2.5w by LED backlight.



3. VESA 75 x 75 mm. wall mount standard.



4. Optional 3" and 7" pole base.



5. Viewing angle adjustable freely with 35 degrees vertically and 70 degrees Horizontally (with pole).