



SeniorSoft®



## SNS-Q3B

### Thermal Receipt Printer

- Support page mode
- Paper shortage alarm
- Support NV logo printing
- With Battery protection mode
- Support Bluetooth dual mode
- Support multiple 1D&2D code printing



Store



Hospital



Café



Logistics



SeniorSoft®

สำนักงานใหญ่

☎ 0-2692-5899

สาขา เอ็ม บี เค เซ็นเตอร์

☎ 0-2048-4500

สาขา ซีคอนสแควร์ ศรีนครินทร์

☎ 0-2656-6089

สาขา เซียร์ รังสิต

☎ 0-2992-6476-77

สาขา เชียงใหม่

☎ 053-850-444

สาขา อุดรธานี

☎ 042-247-455

สาขา หาดใหญ่

☎ 074-246-955-6



@seniorsoft www.SeniorSoft.com



SeniorSoft Development Q



# SNS-Q3B

## Thermal Receipt Printer



Printing		SNS-Q3B
Printing method	Direct thermal	
Paper width	79.5±0.5mm	
Paper roll diameter	50mm	
Paper thickness	0.06 - 0.08mm	
Column capacity	576dots/line;512dots/line	
Printing speed	70mm/s	
Interface	USB+Bluetooth / USB+Wifi / USB+Wifi+Bluetooth	
Character size	ANK,Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots) simplified/traditional Chinese:3.0×3.0mm(24×24 dots)	
Barcode Character		
Extension character sheet	PC347(Standard Europe)/Katakana/PC850(Multilingual)/PC860(Portuguese)/ PC863(Canadian-French)/PC865(Nordic)/West Europe/Greek/Hebrew/East Europe/ Iran/WPC1252/PC866(Cyrillic#2)/PC852(Latin2)/PC858/IranII/Latvian/Arabic/PT151(1251)	
Barcode types	1D:UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128 2D:QR CODE/PDF417	
Buffer		
Input buffer	32Kbytes	
NV Flash	64Kbytes	
Power		
Power adaptor	Input : AC 110V/240V, 50~60Hz ; Output: DC 9V/2A	
Printer input	DC 9V/2A	
Battery	7.4V/2000mAh	
Physical characteristics		
Weight	0.325 KG	
Dimensions	136*116*60mm (D*W*H)	
Environmental Requirements		
Work environment	0~45℃, 10~80% RH	
Storage environment	-10~60℃, 10~90% RH(no condensation)	
Reliability		
Printer head life	50KM	
Driver		
	Windows/Linux/Android/Mac	

